



SR Series Servo Motor Driven Weld Heads


- Programmable speed and positions
- Controlled servo motor actuation eliminates overforce
- Extremely low-end force control (0.25 lbs)
- “Soft Touch” part clamping
- Displacement and force options communication
- Unitip and blade thermode option

Designed for use in automation or benchtop welding, AMADA WELD TECH’s SR Series **servo motor welding heads** offer fast, repeatable electrode motion control for a wide range of resistance welding applications. Two different models are available, each equipped with an easy-to-program, state-of-the-art servo motor controller that allows precise programming of electrode position and speed for up to 32 different weld schedules.

KEY FEATURES

- Write and save up to 32 motion schedules
- “Soft-touch” part clamping minimizes impact force and allows verification of part alignment prior to welding
- Fast follow-up means less weld splash and more consistent welds
- Individual speed control for “stroke to search” and “search to weld” increases flexibility and throughput; good for automation
- Overforce protection ensures concise repeatable force, less weld splash, and reduced part deformation
- Constant applied force - independent of part height - ensures weld repeatability
- Easy programming and fast, efficient schedule adjustment


TYPICAL APPLICATIONS




Solar cell



Pacemaker interconnects



0.002 in diameter magnet wire to gold pad



SERVO MOTOR DRIVEN WELD HEADS

Programmable electrode positions – accurate to 0.004 in

- “Home” position allows for easy access during maintenance
- Electrode in the “Upstop” position in the “Ready” state
- The first level of the footswitch moves the electrode down to the “Search” position at a programmable “Soft-touch” speed
- The second level of the footswitch applies the pre-set welding force, with no overforce
- Programmable “Downstop” inhibits welding if parts are not present

TECHNICAL SPECIFICATIONS

Model Number	SR-071A	SR-072A
Head type	Opposed	Parallel
Force range	0.25 – 16 lbs.*	0.25 – 8 lbs.* per electrode
Weld force method	Spring force setting	
Actuation method	Servo motor	
Electrode stroke	1.5 in max. (0.004 in steps)	
Throat depth inches	4	8
Number of schedules	32 (selectable externally)	
Electrode speed	Start point – Mid point – 8 speeds adjustable by schedule (20-300 mm/s) Mid point – Welding point – 4 speeds adjustable by schedule (7.5-30 mm/s) 8 settings (100, 200, 300, 400, 500, 1000, and 2000 ms, external END signal)	
Power supply	100 - 220 VAC 50/60 Hz	
Welding current	3000 amps @ 2% DC	

*Force range dependent on which spring is used.

WEIGHT & DIMENSIONS

Model Number	SR-071A	SR-072A	Controller
Dimensions (W x D x H)	3.14 in x 8.5 in x 11.8 in (80 mm x 216 mm x 300 mm)	4.7 in x 15.9 in x 10.6 in (120 mm x 404 mm x 270 mm)	2.5 in x 9.6 in x 6.1 in (63.5 mm x 243.8 mm x 154.9 mm)
Weight	7.7 lbs (3.5 kg)	16 lbs (7.3 kg)	6.6 lbs (3 kg)



USA Headquarters and Western Technical Center

AMADA WELD TECH
1820 S. Myrtle Ave. • Monrovia, CA 91016 US • T: (626) 303-5676
info@amadaweldtech.com • www.amadaweldtech.com
ISO 9001:2015 Certified Company • 24/7 Repair Service: 1-866-751-7378

AMERICAS

AMADA WELD TECH
(Eastern Technical Center)
High Point, North Carolina
T: (941) 544-5762
southsales@amadaweldtech.com

AMADA WELD TECH
(Midwest Technical Center)
Detroit, Michigan
T: (248) 313-3078
midwestsales@amadaweldtech.com

AMADA WELD TECH
(Mexico Office)
El Paso, Texas
T: (915) 881-8765
mxsales@amadaweldtech.com

EUROPE
AMADA WELD TECH
GmbH
Munich, Germany
T: +49-89-839403-0
info@amadaweldtech.eu

ASIA

AMADA CO., LTD.
Isehara, Japan
T: +81-463-96-1111
amd_microweld_sales@amada.co.jp

AMADA WELD TECH
SHANGHAI CO., LTD.
Shanghai, China
T: +86-21-6448-6000
jvwu@amadaweldtech.com.cn

AMADA WELD TECH KOREA CO., LTD.
Seoul, Korea
T: +82-31-8015-6810
amadadasales@amadaweldtech.co.kr
sales2@amadaweldtech.co.kr

AMADA WELD TECH TAIWAN CO., LTD.
Taipei, Taiwan
T: +886-3-328-3511

AMADA (THAILAND) CO., LTD.
Bangkok, Thailand
T: +66-2170-5900
info@amada.co.th

AMADA VIETNAM CO., LTD.
Ha Noi, Vietnam
T: +84-4-6261-4583
thuyet@amada.co.jp

AMADA WELD TECH
INDIA PVT., LTD.
Bangalore, India
T: +91-80-4092-1749
info@amadaweldtech.in

Specifications subject to change without notice. Copyright© 2025 AMADA WELD TECH INC.
The material contained herein cannot be reproduced or used in any other way without the express written permission of AMADA WELD TECH INC. All rights reserved.

follow us on:

