

WELTOUCH® CT-110E/CY-210E

AC Timer Secondary Constant Current AC Weld Controls




The Weltouch® AC weld controls with secondary constant current feedback examine each half cycle of the actual weld current flow and compensate for changes in the secondary current during welding. Standard built-in current and conduction degree monitors allow for simultaneous viewing of both programmed and actual weld conditions. Secondary constant current feedback combined with our built-in weld monitors can provide a higher degree of accuracy, confidence and control in AC resistance welding. The CY-210E and the CT-110E are easily adaptable to most existing contactor cabinets.

KEY FEATURES

- Welding mode for high-tensile steel plate
- Easy-to-see LED screen displays weld schedule number, weld current and set time
- Fifteen weld schedules
- Nine current steps
- Primary constant current, secondary constant current and power supply voltage compensation
- Built-in current monitor and conduction angle monitor
- Three counters: production, shot and total

Three-step welding with UPSLOPE and DOWNSLOPE features:



TECHNICAL SPECIFICATIONS

Model	CT-110E Vertical type	CY-210E Horizontal type
Welding power source	220 V / 230 V / 240 V / 380 V / 400 V / 415 V / 440 V / 460 V / 480 V AC -25% +10%, 50/60 Hz (voltage set at time of shipment)	
Control power source	100 V / 120 V / 220 V / 230 V / 240 V AC $\pm 20\%$, 50/60 Hz (voltage set at time of shipment)	
Control method	Primary- or secondary-current feedback constant-current control by phase control using a thyristor, or source-voltage fluctuation compensation control method	
Setting of timers	15 schedules Squeeze, Weld 2, Cool 2, Weld 3, Slope 2, Hold, Off are programmed in 0-99 cycles	
	Weld 1 and Cool 1 0-99 cycles (for CT-110E)	Slope 1 is programmed in 0-9 cycles and Weld 1 and cool 1 is 0-9 cycles (for CY-210D)
Pulsation count	0 – 9 times. Switch to OFF mode.	
Current setting	1.0 – 80.0 kA (maximum current setting: 5.0 – 80.0 kA)	
Control speed	$\frac{1}{2}$ cycle @ secondary constant current control (toroidal coil is required.)	
	1 cycle @ primary constant current control (CT coil is required.)	
	1 cycle @ power supply voltage compensation mode	
Current accuracy (error in full scale)	@ Secondary constant current control 1. Welding power source voltage fluctuation: $\pm 2\%$ for $+10\%/-15\%$ 2. Resistance load fluctuation: $\pm 2\%$ for $\pm 15\%$ 3. Inductive load fluctuation: $\pm 2\%$ for $\pm 15\%$	
Valve output	2 (Schedules 1-7: Valve 1 schedules 8-15: Valve 2) Control voltage (1 A max.) or 24 V DC (0.6 A max.)	Valve 1 or 2 can be selected for 15 schedules.
Step-up	1 series, 9 stages Counter: 0 – 9999	2 series, 9 stages Counter: 0 – 9999
	Counter increase ratio: 50 – 200% of the set current in 1% step	
Current monitor (Available only at constant current control)	1. Upper limit: 0 – 49% 15 schedules 2. Lower limit: 0 – 49% 15 schedules (no monitoring at 0%)	
Conduction angle monitor	1 – 180° 15 schedules (no monitoring at 0°)	
External input signals	INTERLOCK/COUNT RESET (dip switch selectable): If a closed-contact signal is input, the system waits for the power to be turned on or the count to be reset.	INTERLOCK/WELD No. SET (dip switch selectable): If a closed-contact signal is input, the system waits for the power to be turned on when the interlock function is selected.
External output signals	INTERLOCK/COUNT UP (dip switch selectable): Outputs from 2 cycles from when the power is turned on until the power is turned off, or outputs when the counter expires (contact capacity: 110 V AC, 0.5 A)	INTERLOCK/WELD No. ERROR (dip switch selectable): Output from 2 cycles before the power is turned on until the power is turned off, or when a weld-count error occurs (contact capacity: 110 V AC, 0.5 A)
Error output	1. Self-diagnosis error 2. Start input error 3. Current-setting error 4. Current stepper-up ratio setting error	5. Thermostat error 6. Thyristor short-circuit error 7. No-power-supply error 8. Current upper-and-lower-limit error 9. Cond. angle error 10. Full-wave error 11. Total counter- up 12. Insufficient weld count (CY-210D Only) 13. Step-up completion

Note: The conduction-angle monitor does not work in the source-voltage fluctuation compensation control mode.
This monitor cannot be used when the control is used for a welder of the single-phase rectifier type.

SC-181B (THYRISTOR CONTACTOR)

Power requirements for welding power supply	200 – 240 VAC / 380 – 480 VAC, 50/60 Hz
Primary weld current	Duty cycle @ 100%: 1150 A Duty cycle @ 1 sec. in 30%: 1600 A
CT coil	SC-181B-00-00: NA SC-181B-00-10 (built in (for CY-210))
Cooling	Water cooling, Flow rate: 5 L/min
Piping for cooling water	3/8 PT (attachment hose: ID 9 mm)
Protective feature	60°C thermostat

WEIGHT & DIMENSIONS

	CT-110E Vertical type	CY-210E Horizontal type	SC-181B
Dimensions (W x D x H)	4.3 in x 9.8 in x 14 in (110 mm x 250 mm x 355 mm) (excluding fittings)	14 in x 9.8 in x 4.8 in (355 mm x 250 mm x 122 mm)	13.8 in x 15 in x 21.7 in (352 mm x 380 mm x 551 mm)
Weight	9.9 lb (4.5 kg)	9.9 lb (4.5 kg)	30.9 lb (14kg)



USA Headquarters and Western Technical Center

AMADA WELD TECH
 1820 S. Myrtle Ave. • Monrovia, CA 91016 US • T: (626) 303-5676
info@amadaweldtech.com • www.amadaweldtech.com
 ISO 9001:2015 Certified Company • 24/7 Repair Service: 1-866-751-7378

AMERICAS

AMADA WELD TECH
 (Eastern Technical Center)
 High Point, North Carolina
 T: (941) 544-5762
southsales@amadaweldtech.com

AMADA WELD TECH
 (Midwest Technical Center)
 Detroit, Michigan
 T: (248) 313-3078
midwestsales@amadaweldtech.com

AMADA WELD TECH
 (Mexico Office)
 El Paso, Texas
 T: (915) 881-8765
mxsales@amadaweldtech.com

EUROPE
AMADA WELD TECH
 GmbH
 Munich, Germany
 T: +49-89-839403-0
info@amadaweldtech.eu

ASIA

AMADA CO., LTD.
 Isehara, Japan
 T: +81-463-96-1111
amd_microweld_sales@amada.co.jp

AMADA WELD TECH
SHANGHAI CO., LTD.
 Shanghai, China
 T: +86-21-6448-6000
jvwu@amadaweldtech.com.cn

AMADA WELD TECH KOREA CO., LTD.
 Seoul, Korea
 T: +82-31-8015-6810
amadadasales@amadaweldtech.co.kr
sales2@amadaweldtech.co.kr

AMADA WELD TECH TAIWAN CO., LTD.
 Taipei, Taiwan
 T: +886-3-328-3511

AMADA (THAILAND) CO., LTD.
 Bangkok, Thailand
 T: +66-2170-5900
info@amada.co.th

AMADA VIETNAM CO., LTD.
 Ha Noi, Vietnam
 T: +84-4-6261-4583
thuynet@amada.co.jp

AMADA WELD TECH
INDIA PVT., LTD.
 Bangalore, India
 T: +91-80-4092-1749
info@amadaweldtech.in

Specifications subject to change without notice. Copyright© 2025 AMADA WELD TECH INC.
 The material contained herein cannot be reproduced or used in any other way without the express written permission of AMADA WELD TECH INC. All rights reserved.

follow us on:



06/25